



DOD-220

Conventional optical smoke detector

Description

The 200 series of conventional detectors has been developed using the most innovative technical advances. Its completely new design makes the 200 series one of the most elegant on the market, ideal for facilities in which the balance between functionality and aesthetics is necessary.

Detnov's 200 series of conventional detectors is made up of 4 detector types. There are a 58°C rise-of-rate detector, a 78°C heat detector, an optical detector and an optical-heat detector. All of them are compatible with Detnov's CCD-100 and ECO families of conventional control panels.

The DOD-220A smoke detector is based in an optical dark chamber, which, thanks to its design, avoids unwanted air flows and facilitates the guidance of the smoke to the optical sensor. The detection principle is based on the Tyndall effect; the detector goes into alarm status due to the scattered light caused by the smoke particles being received by the optical sensor. The camera is protected to avoid the entrance of dirt and insects. This detector also incorporates compensation algorithms which avoid false alarms due to the dirtiness of the optical chamber, postponing equipment maintenance.

The 200 series detectors require the Z-200 base in order to connect. This connection base includes a blocking option which avoids it being tampered with. A tool is needed to remove the detector from the base.

Detectors in this series have non-polarity technology, facilitating system wiring and saving a huge amount of time in commissioning the system.

Available in black color: DOD-220-B

Features

- Elegant design and low profile
- Dirtiness compensation
- Dirtiness and insect protection
- Two-wire connection without polarity
- Remote indicator port
- Compatible with any conventional fire control panels
- EN 54-7 approved

Applications

Detnov's complete range of 200 series detectors allow reliable fire detection thanks to its advanced analysis technology. Depending on the risk to be protected, you will have to choose the topology of the sensor of the detector, you can choose between: optical, thermal, thermovelocimetric or the combination of said sensors. Detnov's fire detector has been developed to ensure a quick reaction to fires, meeting the highest quality standards and certification required in the market. A unique reliability when detecting and protecting installations to reduce false alarms, being suitable for the most demanding applications.

Technical features

Detector	
Operating voltage:	From 9 to 38VDC
Quiescent current consumption :	< 100 μ A
Alarm current consumption:	< 100 mA
Connections	
2 x 1,5 mm ² twisted cable to a Z-200 base	
Environment	
Operating temperature:	From -10°C to +70°C
Relative humidity:	95% without condensation
IP Index:	IP40
Physical features	
Head (height x Ø):	42 mm x 100 mm
Base (height x Ø):	5 mm x 100 mm
Material:	ABS
Approvals	
EN 54-7	
Certificate number:	0370-CPR-0880

Dimensions

