

THC-B110-P 1 MP Fixed Mini Bullet Camera



- HD 720p bullet camera
- Smart IR: up to 20 m IR distance
- Water and dust resistant (IP66).

▪ Specification

| Camera | |
|----------------------------------|--|
| Image Sensor | 1 MP CMOS image sensor |
| Max. Resolution | 1280 (H) × 720 (V) |
| Min. Illumination | 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR |
| Shutter Time | 1/25 (1/30) s to 1/50,000 s |
| Day & Night | IR cut filter |
| Angle Adjustment | Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360° |
| Signal System | PAL/NTSC |
| Lens | |
| Lens Type | 2.8 mm, 3.6 mm, 6 mm |
| Focal Length & FOV | 92° (2.8 mm), 70.9° (3.6 mm), 56.7° (6 mm) |
| Lens Mount | M12 |
| Image | |
| Image Settings | Sharpness, Contrast, Color Gain, DNR |
| Frame Rate | PAL: 720p@25fps, NTSC: 720p@30fps |
| Day/Night Mode | Auto/Color/BW (Black and White) |
| Wide Dynamic Range (WDR) | DWDR |
| Image Enhancement | BLC |
| AGC | High/Medium/Low/Off |
| Supplement Detection(PIR) | |
| PIR Range | Up to 20 m |
| Interface | |
| Video Output | Switchable TVI/AHD/CVI/CVBS |
| General | |
| Material | Plastic |
| Dimension | 165 mm × 62 mm × 58 mm (6.50" × 2.44" × 2.28") |
| Weight | 150 g (0.33 lb.) |
| Operating Condition | -40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation) |
| Language | English, Chinese |
| Power Supply | 12 VDC ±15% |
| Consumption | Max. 4.2 W |
| IR Range | <30m |
| Approval | |
| Protection | IP66 |

▪ Available Model

THC-B110-P

- **Accessory**
- **Optional**

**HIA-J101
Junction Box**





Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
Technical Support: support@hikvision.com

Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq